

P20

ESPECIFICAÇÕES TÉCNICAS			
Modelo			
Dimensions (w x h)	320mm x 320mm	Resolution (w x h)	16 x 16
Pixel pitch	20mm	Pixel Density	2500/m ²
LED Lamp	Absen LED	Pixel Configuration	1R, 1G, 1B
Panel			
Dimensions (w x h x d) (mm)	1280 x 960 x 180	Module Quantity	12
Physical Resolution (w x h)	64 x 48	Physical Pixels (Total)	3072
Weight / Panel (Kg)	62	Material	Cold rolled steel
Average Power / sqm (watts)	260	Max Power / sqm (watts)	780
Display Data			
ITEM	Width	Height	total
Panel Quantity (pcs)	4	4	16
Screen Area Dimension (m)	5.12	3.84	19.66
Screen Resolution (pixels)	256	192	49152
Total Net Weight (kgs)		992	
Total Average Power (watts)	5111.808	Total Max Power (watts)	15335.424
Parameter	Value		
Brightness	8000 cd / m ²		
Viewing Angle	Horizontal 120 (+60/-60) deg. Vertical 60(+30/-30) deg.		
Minimum Viewing Distance	20 meters		
Brightness Control	256 level		
Gray scale	8192 level		
Refresh frequency	>3000 Hertz		
Driving mode	Static constant current driving		
Input power frequency	50 or 60 Hertz		
Input Voltage	100 ~ 240 Volt		
Blind spot rate	<1/100000		
Lifetime at 50% brightness	100000 hours		
Ingress Protection	Front IP65, Rear IP54		
Operating temperature	- 20 ~ + 50 C		
Operating humidity	10% ~ 90 %		
Control distance	CAT5 cable: <100m; Single mode fiber: < 10 km		
Signal input format	AV, S-Video, VGA, DVI, YpbPr, HDMI, SDI		
Operating system	Windows (2000 / XP / Vista)		

P16

ESPECIFICAÇÕES TÉCNICAS			
Modelo			
Dimensions (w x h)	256mm x 256mm	Resolution (w x h)	16 x 16
Pixel pitch	16mm	Pixel Density	3906/m ²
LED Lamp	Absen LED	Pixel Configuration	1R, 1G, 1B
Panel			
Dimensions (w x h x d) (mm)	1536 x 1024 x 180	Module Quantity	24
Physical Resolution (w x h)	96 x 64	Physical Pixels (Total)	6144
Weight / Panel (Kg)	82	Material	Cold rolled steel
Average Power / sqm (watts)	380	Max Power / sqm (watts)	1150
Display Data			
ITEM	Width	Height	total
Panel Quantity (pcs)	4	3	12
Screen Area Dimension (m)	6.144	3.072	18.87
Screen Resolution (pixels)	384	192	73728
Total Net Weight (kgs)		984	
Total Average Power (watts)	7172.25984	Total Max Power (watts)	21705.5232
Parameter	Value		
Brightness	12000 cd / m ²		
Viewing Angle	Horizontal 120 (+60/-60) deg. Vertical 60(+30/-30) deg.		
Minimum Viewing Distance	16 meters		
Brightness Control	256 level		
Gray scale	8192 level		
Refresh frequency	>3000 Hertz		
Driving mode	Static constant current driving		
Input power frequency	50 or 60 Hertz		
Input Voltage	100 ~ 240 Volt		
Blind spot rate	<1/100000		
Lifetime at 50% brightness	100000 hours		
Ingress Protection	Front IP65, Rear IP54		
Operating temperature	- 20 ~ + 50 C		
Operating humidity	10% ~ 90 %		
Control distance	CAT5 cable: <100m; Single mode fiber: < 10 km		
Signal input format	AV, S-Video, VGA, DVI, YpbPr, HDMI, SDI		
Operating system	Windows (2000 / XP / Vista)		

P10

Parameter	Value	Unit
Model	A1088	-
Pixel pitch	10.66	mm
Brightness	8000	nit
Panel dimensions (W x H x D)	1536 x 1024 x 175	mm
Panel dimensions (W x H x D)	60.47 x 40.31 x 6.89	inch
Panel material	Steel	-
Weight	82	kg
Weight	180.8	lbs
Pixel configuration	1R1G1B	-
Module dimensions (W x H)	256 x 256	mm
Module dimensions (W x H)	10.08 x 10.08	inch
Pixel matrix per panel	144 x 96	pixels
Pixel density	8789	pixels / sq.m.
Refresh rate	≥1200	Hz
Gray scale per color	8192	level
Colors	549 Billion	-
Viewing angle (H/V)	120/60	deg.
IP rating (Front / Rear)	IP65/IP54	-
Power consumption (max / avg)	750/250	W/sq.m.
Input voltage (AC)	110 ~ 240	v
Operanting temperature	-20 ~ + 50	°C
Operanting humidity	10% ~ 90%	-
Source compatibility (with video processor)	AV, S-Video, VGA, DVI, HDMI, SDI, DP	-

P12 – Painel Flexivel Indoor

Visual characteristics		
Pixel pitch	12.5	mm
Pixel configuration	3LN 1 SMD	-
Brightness	≥2500	nit
Refresh frequency	5000	Hz
Gray scale	65536	Level
Transparent rate	12%	-
IP rating (Front / Rear)	IP65 / IP 65	-
Distribution box IP Rating (Front / Rear)	IP54 / IP 54	
Viewing angle (H/V)	140 / 145	°
Power consumption (max/avg) 360/120	349/118	W/m ²
Modular characteristics		
Cabinet size (WxHxT)	300 x 4500 x 37,5	Mm
Module dimensions (WxHxT)	300 x 72 x x 37,5	Mm
Pixel matrix	24 x 360	Pixels
Pixel density	6400	Pixels / sg.m.
Panel material	PC	-
Cabinet Curved radius (inward / outward)	477/239	Mm
Environment		
Operating temperature	-20~ + 50	°C
Operating humidity	10% - 90%	-
Signal input format (with video processor)	AV, S-Video, VGA, DVI, YPbPr, HDMI, SDI	-